

OVERVIEW



1. Power connector	5. Power button
2. HDMI	6. SD card reader
3. Thunderbolt 4	7. USB-A (USB 5Gbps)
4. Headphone / microphone combo jack (3.5mm)	8. USB-A (USB 5Gbps), Always On



PERFORMANCE

Processor

Processor Family

Intel® Pentium® or 12th Generation Intel Core™ i3 / i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	ds Base Frequency Max Frequency		Cache	Processor Graphics
Pentium Gold 5 (1 P-core + 4 E- 8505 core) 6		6	P-core 1.2GHz / E-core 0.9GHz	P-core 4.4GHz / E-core 3.3GHz	8MB	Intel UHD Graphics
Core i3-1215U 6 (2 P-core + 4 E-core) 8		8	P-core 1.2GHz / E-core 0.9GHz	P-core 4.4GHz / E-core 3.3GHz	10MB	Intel UHD Graphics
Core i5-1235U 10 (2 P-core + 8 E-core)		12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.4GHz / E-core 3.3GHz	12MB	Intel Iris® Xe Graphics
Core i7-1255U 10 (2 P-core + 8 E-core) 12		12	P-core 1.7GHz / E-core 1.2GHz	P-core 4.7GHz / E-core 3.5GHz	12MB	Intel Iris Xe Graphics

Operating System

Operating System**

- Windows® 11 Home Single Language in S mode
- Windows 11 Home in S mode
- Windows 11 Pro

Graphics

Graphics**

Graphics	Туре	Memory	Key Features
Intel UHD Graphics	Integrated	Shared	DirectX® 12.1
Intel Iris Xe Graphics	Integrated	Shared	DirectX 12.1

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and Thunderbolt™)

- HDMI supports up to 4096x2160@30Hz
- Thunderbolt supports up to 5120x3200@60Hz

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots, single-channel (4GB models)
- Memory soldered to systemboard, no slots, dual-channel (8GB or 16GB models)

Memory Type

LPDDR4x-4266

Storage

Storage Support[1]

One drive, up to 1TB M.2 2242 SSD or 512GB M.2 2280 SSD

Storage Slot



One M.2 2280 PCIe® 4.0 x4 slot

Storage Type**

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4	128GB
M.2 2242 SSD	PCIe NVMe, PCIe 4.0 x4	256GB / 512GB / 1TB
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	512GB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Front-facing stereo speakers, 2W x2, optimized with Dolby® Audio™

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

Sensor

Sensors

- · Accelerometer (G) sensor
- · Hall sensor

Battery

Battery

Integrated Li-Polymer 52.5Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[1]

Max Battery Life[2]

• WUXGA models:

MobileMark® 2018@200nits: 9 hr

Local video (1080p) playback@150nits: 13.5 hr

2.2K models:

MobileMark 2018@200nits: 7.5 hr

Local video (1080p) playback@150nits: 10.5 hr

2.8K models:

MobileMark 2018@200nits: 7 hr

Local video (1080p) playback@150nits: 10 hr

Notes:

[1] Rapid Charge Boost is only effective in hibernates or fully shutting down the computer.

[2] All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz



DESIGN

Display

Display**

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
14"	WUXGA (1920x1200)	Multi- touch	IPS ^[1]	300nits	Glossy	16:10	800:1	45% NTSC	60Hz	85°/85°/85°	TÜV Low Blue Light (Software), Glass
14"	2.2K (2240x1400)	Multi- touch	IPS ^[2]	300nits	Glossy	16:10	1,500:1	100% sRGB	60Hz	85°/85°/85°	TÜV Low Blue Light (Hardware), Glass
14"	2.8K (2880x1800)	Multi- touch	OLED	400nits	Glossy	16:10	100,000:1	100% DCI- P3	60Hz	87.5°/87.5°/87.5°/87.5°	TÜV Low Blue Light (Software), Glass

Touchscreen

GFF (Glass-Film-Film) or OGS (One Glass Solution) multi-touch, supports 10-point touch

Notes:

[1], [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen**

- Lenovo Digital Pen with replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity. For more information, please read <u>Lenovo Digital Pen Overview</u>
- Lenovo Digital Pen without replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity. For more information, please read <u>Lenovo Digital Pen Overview</u>
- No pen (purchase separately)

Keyboard

6-row, multimedia Fn keys

Keyboard Backlight

- · LED backlight
- · Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)[1]

Models	Dimensions
Metal models	313.1 x 224.9 x 17.4 mm (12.32 x 8.85 x 0.69 inches)
Plastic models	313.1 x 224.9 x 17.8 mm (12.32 x 8.85 x 0.70 inches)

Weight^[2]

Models	Weight
Models with metal	Starting at 1.5 kg (3.31 lbs)
Models with plastic	Starting at 1.55 kg (3.42 lbs)

Case Color**

IdeaPad Flex 5 14IAU7



- · Cloud grey
- Stone blue
- Storm grey

Surface Treatment**

- Aluminium stamping (anodized with sandblasting)
- Painting

Case Material**

- Aluminium (top), PC-ABS + 40% GF (bottom)
- PC-ABS + 40% GF (top), PC-ABS + 40% GF (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**[1]

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.1, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card^[2]

Notes:

- [1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.
- [2] Wi-Fi 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 1x USB-C® (Thunderbolt 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 1.4a
- 1x HDMI 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x SD card reader
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions are supported via Thunderbolt.

For more compatible docking solutions, please visit Docking for IdeaPad® Flex 5 14IAU7

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

Touch style fingerprint reader on palm rest



BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password
- Self-healing BIOS

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ENVIRONMENTAL

Operating Environment

Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitudo

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories[1]

None

Notes:

[1] For more compatible accessory solutions, please visit <u>Accessories for IdeaPad Flex 5 14IAU7</u>.

CERTIFICATIONS

Green Certifications¹¹

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

Notes:

IdeaPad Flex 5 14IAU7



[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

Other Certifications

Other Certifications

- Models with 2.2K panel: TÜV Rheinland® Low Blue Light (Hardware Solution)
- Models with 2.8K OLED, WUXGA panel: TÜV Rheinland Low Blue Light (Software Solution)
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







intel





intel. intel.



intel



intel.